

Hamilton Beach
COMMERCIAL

HBF600R Culinary Blender

High Performance

Chop, grind,
blend, puree,
emulsify

with unlimited options

EXPEDITOR™ family of blenders

Unique one-touch chopping function with speed control gives chefs ultimate control over food consistency

Powerful 3 peak* HP motor lets chefs chop salsas and compotes, grind flours, puree soups, emulsify dressings and more

Intuitive touchpad with variable speed dial to control consistency and speed with precision

64 oz. / 1.8 L BPA-free copolyester container

Extremely durable all-metal drive coupling with jar pad sensor to help extend coupling life

*input power



For more Good Thinking® visit hamiltonbeachcommercial.com





Large Dosing Cup
Makes adding liquids for emulsions easy while blending

64 oz. / 1.8 L BPA-Free Copolyester Container
With laser-etched measurements that last a lifetime

Patented Wave~Action® System
Keeps ingredients circulating through the blades to ensure that contents are fully emulsified

Adjustable Speed Dial
Offers the operator variable speed options



One-Touch Chopping Function
Cycles between low speed and operator-selected high speed



Sealed Lid Prevents Leaks
With easy-to-lift tab and dosing cup



Jar Pad Sensor
4 magnetic connections prevent blending unless container is on correctly



Temperature Gauge
Alerts operator if motor overheats while blending back-to-back batches

Powerful 3 Peak* HP Motor
Lets chefs chop salsas and compotes, grind flours, puree soups, emulsify dressings and more

*input power

HBF600R SERIES HIGH-PERFORMANCE CULINARY BLENDER

SPECIFICATIONS:



Standard: Unit comes with base, one 64 oz. / 1.8 L container, 4 oz. / 120 ml dosing cup and removable jar pad
Controls: Touchpad with variable speed, high, chop and pulse
Motors: 3 peak* HP
Weight: 15.01 lbs / 6.81 kg (shipping)
Warranty: 3 years parts & labor. Lifetime warranty on blade and motor drive coupling.

HBF600R (120 V)

Electrical: 120 V, 60 Hz, 12.5 A
Cord Length: 6.2 ft / 1.9m



European and UK cordset included HBF600R-CE (230 V)

Electrical: 220-240 V, 50-60 Hz, 1200 W
Cord Length: 1.9m / 6.2 ft



RoHS COMPLIANT