

Project: _____
 Model #: _____
 Item #: _____ Qty: _____
 Approval: _____

460 Southport Commerce Blvd.
 Spartanburg SC 29306
 Phone: 864-574-6004
 Toll Free: 1-888-532-2816
 sales@ojedausainc.com
 service@ojedausainc.com
 www.ojedausa.com



BUNKER FREEZER

NBH-68



Custom Graphics
 Available Upon Request

R-290 REFRIGERANT

Equipped with R-290 refrigerant, an eco-friendly alternative that meets the EPA's environmental impact regulations.

STEEL CONSTRUCTION

Robust steel construction minimizes the use of plastic materials resulting in an environmentally friendly design.

SLIDING LIDS

Low-E tempered sliding glass lids reflect light and reduce the heat load inside the cabinets. Each unit comes with a lock and keys for added security.

HIGH IMPACT ABS FRAME

Made of a high impact durable plastic, this frame assures a long-term life span.

ADJUSTABLE THERMOSTAT

Freezers are equipped with a mechanical thermostat that allows the users to adjust temperature that best fits their products needs. Set from factory at -4°F.

INTERNAL LED LIGHTING

LED lighting in our bunker freezers ensures products are beautifully illuminated, enhancing visibility and creating an appealing display for customers.

CASTERS

Equipped with casters that allow easy and fast movement in the store.

TOP LIGHT BAR

Optional top light bar for custom graphics.

OPERATION TEMPERATURE

Low temp: -10°F to 0°F.

Dimensions			Baskets	HP	Voltage	NEMA Config	Amps	Crated Weight	Refrigerant
W	D	H							
68.4"	26.4"	34.3"	7	1/4+	120	5-15P	4	380 lbs	R-290
1738 mm	671 mm	872 mm	Net Capacity (cf): 19		Energy Consumption: 2.82 kWh/24 hrs				

*Inches rounded up one decimal place. *Specifics may change without notification.

BUNKER FREEZER

NBH-68

CABINET CONSTRUCTION

- High-density, CFC-Free, polyurethane insulation.
- High impact ABS top frame.
- Exterior: white galvanized metal cabinet with powder coated painted surface.
- Interior: white easy to clean pre-painted steel.
- Rated for Ice Cream.

Lids

- Removable Low-E tempered sliding glass lids.
- Includes Lock and set of keys.

Baskets

- 7 removable baskets.
- Basket Dimension 8.6" W x 21.7" D x 20.3" H.

OPERATING CONDITIONS

- The unit is best suited for an environment where temperatures remain below 75°F and humidity does not exceed 55%.
- Areas with direct sunlight should be avoided.

ELECTRICAL

- 110/120 standard volt system.



LIGHTING

- LED interior lighting.

REFRIGERATION

- R-290 refrigerant.
- Cold wall refrigeration system.
- Mechanical thermostat.
- Easy to reach components for maintenance.

ACCESSORIES

- Two ring tub holders.
- Dip well.
- Top light bar.
- Custom Graphics.

OPTIONAL ACCESSORIES


DIP WELL



2 RING TUB HOLDERS



DIMENSIONAL DRAWING



*Inches rounded up one decimal place. *Specifics may change without notification.



www.ojedausa.com