	Project Name: _		AIA#:
Model #:		Location:	



Colobe Premium Heavy-Duty **Manual Slicer**

Precise - Powerful -**Premium Construction**

The heavy-duty S-Series line of premium slicers from Globe delivers precision, performance, industry-leading convenience, superior cleanability and lasting value.



Removable Knife makes cleanup easier while providing more operator protection













Model

☐ S13 (Standard Model)

S13 Standard Features

- Patented anodized aluminum design & construction for quick and easy cleaning
- Patented indexing system enables accurate and precise slice thickness adjustment up to 1-1/8"
- 13" steel knife with hardened edge provides quality slices and higher yield
- Tilting carriage for superior cleaning access that accommodates large products like prosciutto, mortadella and
- Advanced meat grip design for superior product hold
- 1/2 HP continuous use knife motor combined with the high efficiency knife drive system delivers optimum power
- No Voltage Release prevents inadvertent reactivation of slicer in the event of power interruption
- Interlock prevents slicer from operating without the knife cover in place
- Top mounted, removable grit stone sharpening system enables quick and easy sharpening and cleaning
- Integrated kickstand to facilitate ease of cleaning

Warrantv

Two year parts and labor

Factory Installed Options

- KNIFE-RMV Removable Knife includes removal tool
- CARRIAGE-RMV Removable Carriage
- FRZN Serrated knife in lieu of standard knife and additional modifications; for slicing product between 20° and 32° F. Max slice width 1/8"
- CORR Correctional Package
- SSK Stainless Steel Knife in lieu of Carbon Steel

Optional Accessories

- S-FENCE Food Fence
- S-FENCEHI High Food Fence
- S-VEGHOP Vegetable Hopper
- SC-LARGE Slicer Sanitation Cover
- S-SLAWTRAY Slaw Tray
- S-LEGS 2.5" Extension Legs
- S-XDSLM Extended Warranty

To select factory-installed options and accessories, see back

Approved by: _

Nobe Premium Automatic Slicer **Factory Installed Options**



TAMPER-PROOF TORX® SCREWS



NON-REMOVABLE SLIDE ROD

DOUBLE SERRATED KNIFE FRONT

DOUBLE SERRATED KNIFF BACK




FULLY ENCLOSED BOTTOM

Correctional Package (CORR)

- Available for S13 and S13A only
- External fasteners are tamper resistant 6-point star shaped Torx® screw heads which can only be removed with a special driver bit supplied with the slicer
- Knife cover, carriage tilt and sharpener blank secured with Torx® screws
- Secured sharpener blank allows real sharpener to be secured away from slicer
- Slicer feet can be secured to table
- Slide rod and end weight are non-removable
- Bottom cover is secured with Torx® screws

Frozen Package (FRZN)



- Slices frozen product between 20° and 32° F, as well as most non-frozen products, max slice width 1/8"
- Patent-pending indexing system enables accurate and precise slice thickness adjustment up to 1/8"
- 13" double serrated steel knife with hardened edge provides quality slices and higher yield
- Slices 30 strokes per minute in automatic mode

Removable Carriage Package (CARRIAGE-RMV)

- Carriage easily lifts off slicer for cleaning
- Captive knob keeps carriage secure during slicing
- Carriage is removable without tilting, saving valuable space



- Knife is secured in tool for operator protection
- Tool easily removes knife for more access under the knife and faster, easier cleanup
- Knife and removal tool are dish machine safe

Stainless Steel Blade (SSK)

- · For high acid content applications as found in vegetable and fruit preparation
- Helps protect slicer from corrosion caused by extreme moisture applications (meatrooms)
- Also recommended for tempered (semi-frozen) meat cutting





STAINLESS STEEL BLADE

flobe Premium Automatic Slicer **Accessories**







☐ S-FENCE High food fence (12.125" x 1.125")



☐ S-VEGHOP Vegetable Hopper



☐ SC-LARGE Slicer Sanitation Cover



☐ S-SLAWTRAY Slaw Tray



S-LEGS 2.5" Extension Legs (set of 4)




☐ S-XDSLA **Extended Warranty**


S-Series Features, Options & Accessory Guide

FEATURE	S13	S13A	SG13	SG13A
Knife Cover Interlock (Machine will not turn on)			•	
Carriage Tilt Interlock (Machine will not turn on)				•
Home to Start (Carriage must be in Home position for blade to rotate)			•	•
Home Return			•	•
Time Out (Blade will stop running if not in use)*			•	•
Close to Stop (Blade will stop running when gauge plate is closed)			•	
LCD Display		•	•	•
Site Diagnostics		-	•	
System Counters		•	•	•
No Volt Release	-	-	•	
Slicing Length Settings		2		3
Slicing Speed Settings		2		4
CORR - Correctional Package (Factory Option)	•	•	•	•
KNIFE-RMV - Removable Knife (Factory Option)	-	-		
CARRIAGE-RMV - Removable Carriage (Factory Option)	•	•	•	•
FROZEN - Frozen Package (Factory Option)	•	•		

^{*}Time Out is programmable. Factory setting is 30 seconds.

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodeguip.com





UNIT: Inches

Drawings available through KCL. www.kclcad.com

SPECIFICATIONS												
Model	Motor	Volts	Amps	NEMA Plug Type	Drive Type	Slicing Vol. / Day	Cheese Slicing	Blade Diameter	Max Slice	Produ D (Diameter)	ct Cutting Ca H (Height)	apacity W (Width)
S13	1/2 HP	115-60-1	2	5-15 (1)	Poly-V Belt	All Day	0 100%	13" (33.02 cm)	1-1/8" * (2.857 cm)	8" (20.32 cm)	13.75" (35 cm)	11" (27.94 cm)
S13-05	1/2 HP	220-60-1	1	6-15P 급	Poly-V Belt	All Day	0 100% Time	13" (33.02 cm)	1-1/8" * (2.857 cm)	8" (20.32 cm)	13.75" (35 cm)	11" (27.94 cm)
S13-07	1/2 HP	220-50-1	1	CEE7/7 😯	Poly-V Belt	All Day	0 100%	13" (33.02 cm)	1-1/8" * (2.857 cm)	8" (20.32 cm)	13.75" (35 cm)	11" (27.94 cm)

Cord & Plug: Attached 7 ft. flexible 3-wire cord with molded plug fits a grounded receptacle.

DIMENSIONS | SHIPPING INFORMATION

Reinforced carton for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment. Shipped on a pallet. Freight class 85.

Model	Max Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
S13	36.5" W x 28.5" D x 25.5" H	114 lbs.	31.5" W x 31.5" D x 31.5" H	135 lbs.
	(92.63 cm x 75.08 cm x 64.8 cm)	(51.71 kg)	(80 cm x 80 cm x 80 cm)	(61.24 kg)

FACTORY INSTALLED OPTIONS:

- ☐ KNIFE-RMV Removable Knife includes removal tool
- ☐ CARRIAGE-RMV Removable Carriage
- FRZN Serrated knife in lieu of standard knife and additional modifications
- CORR Correctional Package
- SSK Stainless steel knife in lieu of Carbon Steel

OPTIONAL ACCESSORIES:

- ☐ S-FENCE Food Fence
- ☐ S-FENCEHI High Food Fence
- ☐ S-VEGHOP Vegetable Hopper
- ☐ SC-LARGE Slicer Sanitation Cover
- S-SLAWTRAY Slaw Tray ☐ S-LEGS - 2.5" Extension Legs
- ☐ S-XDSLM Extended Warranty





KNIFE-RMV

Constructed of anodized aluminum. 1/2 HP motor with overload protection and 13" hardened steel knife. Patent-pending indexing system with slice thickness adjustment up to 1-1/8". Top mounted removable sharpener with grit stone wheel and plate. Tilting carriage. Adjustable cut length and speed (model S13A & SG13A only). Slicer is ETL listed. No Voltage Release and Knife cover Interlock. Two year parts and labor warranty.

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodequip.com

^{*}Max slice thickness for frozen is 1/8"