

SOUP COOKING & WARMING EQUIPMENT

The Glenray® Kettle

The Glenray® Kettle is a 10.5 quart (9.9 litre) soup warming and holding kettle featuring adjustable temperature control and a stainless steel hinged lid. The kettle is available in black or stainless steel. Each kettle is shipped with a stainless steel food insert and a stainless steel ladle. NSF listed for rethermalization. Kettle is 15" H and 13" diameter (381 mm x 330 mm).



Optional hinged, split lid makes service easier—no need to fully remove lid!



	Model #	Description	Voltage	Wattage	Ship Wt. lbs./kgs.
10.5 qt.	1021805	Black	120	400	15/7
10.5 qt.	1021806	Stainless steel	120	400	15/7

Accessories	Model #	Description	Ship Wt. lbs./kgs.
	1410867	Standard lid assembly	2/1
	1921850	Hinged split lid	2/1
	1910807	Stainless steel food insert, 10.5 qt.	4/2
	1910804	Collar, black	1/5
	1921848	Collar, stainless steel	1/5



The Dual Food Warmer

Cook two soups at one time! Features individual temperature control switches, dual heating elements, hinged lids and transport collars. Easy-to-clean stainless steel exterior is great for front or back of house operation. 8 or 12 quart (7.6 or 11.4 litre) stainless steel food inserts. 8 quart is NSF listed for rethermalization.



Dishwasher-safe hinged lid assembly.



	Model #	Dimensions inches (mm)	Wattage	Ship Wt. lbs./kgs.
8 qt.	1014697	16 H x 22 W x 12 D (406 x 559 x 305)	550 x 2	26/12
12 qt.	1014788	16 H x 22 W x 12 D (406 x 559 x 305)	550 x 2	26/12

Accessories	Model #	Description	Ship Wt. lbs./kgs.
	1406804	Lid assembly, for 8 qt.	1/5
	1406806	Lid assembly, for 12 qt.	2/1
	1906625	Stainless steel food insert, 8 qt.	3/1
	1906626	Stainless steel food insert, 12 qt.	4/2
	1415773	Transport collar, 8 qt.	1/5
	1415770	Transport collar, 12 qt.	1/5

Note: NSF's Rethermalization Standards require an appliance to heat a test mixture from 40°F to 165°F (4°C to 74°C) within two hours.

Induction Cooktop

An easy, clean, safe (no open flames), economical and energy-efficient way to cook and maintain food temperatures, especially on buffet lines. Built for medium to heavy-duty use, this unit features 15 power levels, temperature range from 140°F to 428°F, attractive stainless steel case, minute timer up to 120 minutes, automatic shut-off, small object detector and overheat protection. Unit measures 4-7/8" H x 17-5/16" L x 13-5/16" W (124 x 450 x 338 mm).



Model #	Description	Voltage	Wattage
1022750	Induction cooktop	120	1800
1022751	Induction cooktop	240	3500