

WE RAISE THE BAR. WE SET THE STANDARD.

Item Number **Project** Quantity

60 Quart (qt.) Floor Model Mixer

MADE IN THE USA

Model:

SRM60+: 60 gt. FLOOR MODEL MIXER





Standard Accessories:

- 15 minute timer
- Wire whip
- Dough hook
- Batter beater
- 60 at. stainless steel bowl
- Ingredient chute
- Bowl scraper
- Power bowl lift

Optional Accessories:

- Splash ring
- 60 qt. pastry knife
- Cover
- Four wing beater
- Bowl truck

- Heavy duty SS wire whip
- Sweet dough beater

Optional Attachments:

- VS9 vegetable slicer with adjustable knife
- VS9H vegetable shredder with plate holder and 3/16" plate (additional plate size variations, grater plates, and julienne plate available)
- ALMFC12 meat and food grinder

Warranty:

Two year, on-site parts and labor

Features:

- 3 hp capacitor start motor
- Variable Speed Drive: 4 fixed speeds or any speed in-between
- Change speeds without having to stop the
- Two-piece, stainless steel, dishwasher safe safety guard
- #12 Power Take Off (PTO) hub
- Heavy-duty stainless steel bowl
- Interlock switches protect operator from injury if safety guard is open or bowl is lowered
- Hardened alloy gears in transmission
- Low voltage protection prevents accidental start up after power failure
- Durable NSF approved hybrid epoxy/polyester powder coat finish



Univex Corporation www.Univexcorp.com 3 Old Rockingham Rd Salem, NH 03079 United States of America

TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249

Printed in U.S.A.

Univex Corporation


Floor Model Mixer


SRM60+ Mixer




60 Quart Floor Model Mixer

SRM60+







Shipping Information						
Net Weight Shipping Weight Overall Dimensions						
750 lbs (340.2Kg)	1000 lbs (453.6Kg)	66" (167.6cm) H x 41" (104.1 cm) W x 51" (129.5cm) D*				
*The and dimensions of the pallet are included in the weight and dimensions above.						

Electrical Information (60Hz) Attached 6 foot cord								
Standard	208-240	1	16.0-16.8	6-20P				
Optional	208-240	3	8.0-8.5	L15-20				
	460	3	4	L16-20				

Mixer Speeds							
Speed	1	2	3	4			
Beater Shaft (RPM)	119	166	275	498			
PTO (RPM)	93	132	214	390			

Bowl Capacity: 60 qts. (56.7 Liters)

Motor: 3 hp capacitor start

Controls: Momentary contact stop & start buttons

and contactor

Bowl Lift: Power bowl lift standard OR Ergonomic hand operated

crank, self locking in top and bottom position

Lubrication: Oil bath

Transmission: Oil bath featuring hardened alloy gearing and

torque sensing variable speed pulleys

Power Take Off (PTO): #12 Hub



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249

Printed in U.S.A. 07/2024