APPLICATION: PRODUCT NAME: 8" C/C BACKSPLASH MOUNT PRE-RINSE SPRING STYLE WITH ADD-ON FAUCET JOB NAME: MODEL: 48887 WITH 6" SWING SPOUT QUANTITY: ITEM NO. **OPTIONS OR MODIFICATIONS:** ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH □ IN-LINE DUAL CHECK VALVE ☐ BRUSH ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE □ VANDAL RESISTANT KIT ■ OTHER EZ INSTALL ADAPTERS **FEATURES** MAIN CONTROL VALVE * 8" C/C BACKSPLASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * SWIVELLING SEAT DISKS * HOT SIDE STEM - RIGHT HAND CHECK * COLD SIDE STEM - LEFT HAND CHECK * STAINLESS STEEL SEATS, SEAT SCREWS, AND 38" HANDLE SCREWS [965|mm] HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE 6" [152.4mm] * REPAIRABLE IN-FIELD WITH SIMPLE TOOLS **ULTRA SPRAY VALVE** * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI [305mm] * CLEANS FASTER - TEST PROVEN 1/2" SLIP JOINT -* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK 12" 12-7/8" * INTERCHANGEABLE - FITS ALL BRANDS [305mm] 9" [326mm] 4-1/4" [228mm] [105mm] WAL BRACKET * ADJUSTS FROM 2" TO 12" SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. 2-3/8" * PRESSURE: 200 PSI MAX. STATIC [60mm] 8" [203mm] 1-3/8" -SHIPPING WEIGHT 12" (MAX) [34mm] * 15.0 LBS [305mm] **ROUGH-IN** Ø7/8" [22mm] [203mm] FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238

EPAct 2005 Compliant

B

ANSI/A112.18.1M

information@fisher-mfg.com - www.fisher-mfg.com

SPEC.

PRHB-SPA-8BZZL