



# CLASSIC SERIES ESPRESSO MACHINES

Project	Date	Models	Item#	Quantity
		CS1-110, CS1-220, CS2-220, CS3-220		



model CS1-110




model CS2-220

## Features

- Easy Espresso!
- Elegant design combines a metallic curved front with diamond black sides.
- Pressure gauge/sight glass allows easy monitoring.
- Separate independent auto back flushing allows convenient machine maintenance.
- Stainless steel exchange boiler provides temperature stability.
- Hot water and steam knob features two easy-to-use methods of operation.
- Steam pressure release function ensures safe operation.
- Boiler low water safety feature prevents machine from overheating without water.
- Hot water dispensing wand.
- Raised group heads fits tall, take-away cups.

## Models & Dimensions

### Classic Series Espresso Machines



## Specifications

Model	Number of Heads	Boiler Size	Electrical	Product Dimensions (H x W x D)	Ship Weight
<b>CS1-110</b> (1008-000)	1 Group	6 qts. (5.7L)	110/120V / 2 kW 18 A / 1 Ph	25" x 19" x 20.5" (63 cm x 48 cm x 52 cm)	104 lbs. (47 kg)
<b>CS1-220</b> (1008-001)	1 Group	6 qts. (5.7 L)	220/240V / 2 kW 10 A / 1 Ph	25" x 19" x 20.5" (63 cm x 48 cm x 52 cm)	104 lbs. (47 kg)
<b>CS2-220</b> (1008-002)	2 Groups	13 qts. (12.3 L)	220/240V / 4.7 kW 20 A / 1 Ph	25" x 28" x 20.5" (63 cm x 71 cm x 52 cm)	115 lbs. (52 kg)
<b>CS3-220</b> (1008-003)	3 Groups	19 qts. (18 L)	220/240V / 6.5 kW 27 A / 1 Ph	25" x 37" x 20.5" (63 cm x 95 cm x 52 cm)	148 lbs. (67 kg)

**Plumbing:** Unit attaches to 0.75" (1.9 cm) hose connection, 0.5" (1.3 cm) water line required. Water pressure between 20PSI and 120 PSI. Use regulator for higher pressure.

**Note:** 4" (10.2 cm) clearance required on side and rear.



Grindmaster-Cecilware™ 4003 Collins Lane, Louisville, KY 40245 USA

Tel: +1.502.425.4776 / 800.695.4500 (USA & Canada only) • Fax: +1.502.425.4664 • [www.gmcw.com](http://www.gmcw.com) • Email: [info@gmcw.com](mailto:info@gmcw.com)