

# CONVECTION OVEN

### CONCEPT

#### **FULL SIZE CONVECTION OVENS**

High capacity, consistent quality baking in a small footprint

- ☐ Two speed rear mounted fan motor for greater variety of baking applications
- ☐ Reversing turbine fan for quick and uniform baking
- ☐ Manual steam with push-button operation
- ☐ Stainless steel exterior and interior construction
- ☐ Thermostatic temperature control up to 570°F
- ☐ 120 minute timer with audible end-of-cycle signal
- ☐ Cool-to-the-touch double glass door removable for easy cleaning
- ☐ Internal lights allow for cooking visibility
- ☐ Four chrome plated wire shelves included
- ☐ Compact footprint



EP 800 Proofer

- · Stainless steel interior and exterior
- Automatic steam production
- · Dough rise: 85°F in 2 hours
- · 8 wire racks included

#### MAGNUM

**FC-100 FC-103** 208/240 V, 1PH 208/240 V, 3PH



CAPACITY: FC-100/FC-103, FC-100G/FC-103G

- (4) wire shelves  $25 \frac{3}{4}$ "x16" (included)
- (4) full size pans (18"x26"x1")

#### MAGNUM PLUS

FC-100G

FC-103G

208/240 V, 1PH

208/240 V, 3PH



\*TurboQuartz feature



#### WITH TURBOQUARTZ® FEATURE

features infrared overhead broiling elements - convection and broiling modes operate separately or in combination














## FULL SIZE CONVECTION OVEN MODEL FC-100/FC-103



## FULL SIZE CONVECTION OVEN WITH BROILER - TURBOQUARTZ® MODEL FC-100G/FC-103G


All features of FC-100 with infrared heating elements overhead - convection and broiling modes operate separately or in combination


#### **SERVICE CONNECTIONS AND NOTES:**

- 1 cold water supply: 1/2" hose connection
- electrical connection:

  FC-100/FC-100G 6 ft. cord and plug

  FC-103/FC-103G terminal block





INSTALLATION CLEARANCE ALL MODELS: 4" EACH SIDE, TOP AND BACK

#### SPECIFICATIONS

MODEL	ELECTRICAL	EXTERIOR DIMENSIONS	INTERIOR DIMENSIONS	SHIPPING WEIGHT	NEMA PLUG
FC-100	208/240V, 1PH, 6KW, 25/29 Amps	32 <sup>1</sup> / <sub>2</sub> "Wx30"Dx22 <sup>1</sup> / <sub>2</sub> "H (add 4" for legs)	26"Wx18 <sup>1</sup> /2"x13 <sup>1</sup> /2"H	195 lbs	6-50P
FC-103	208/240V, 3PH, 6KW, 15/18 Amps				no plug
FC-100G	208/240V, 1PH, 6KW, 25/29 Amps	32 <sup>1</sup> / <sub>2</sub> "Wx30"Dx22 <sup>1</sup> / <sub>2</sub> "H (add 4" for legs)	26"Wx18¹/₂"x12"H	195 lbs	6-50P
FC-103G	208/240V, 3PH, 6KW, 15/18 Amps				no plug
EP800	208/240V, 1PH, 1400W, 6/7 Amps	31 <sup>1</sup> / <sub>2</sub> "Wx25 <sup>1</sup> / <sub>4</sub> "Dx36"H	(8) 23 <sup>5</sup> / <sub>8</sub> "Wx15 <sup>3</sup> / <sub>4</sub> "D Shelves	210 lbs	6-15P

WARRANTY: Limited one year parts and labor



100 NIANTIC AVENUE; SUITE 104 PROVIDENCE, RI 02907

TEL: (401)273-3300 FAX: (401)273-3328 E-mail: sales@equipex.com

www.equipex.com